

PRODUCT DATASHEET FLASHLIGHT TACTICAL IP22

FLASHLIGHT TACTICAL | Outdoor mobiles

Areas of application

- Multifunctional



Product benefits

- 5 operating modes: 1 press: bright light 300 lm, 2nd press: soft light 100 lm, 3rd press: dim light 60lm, 4th press: SOS mode, 5th press: flashing mode
- 1,5 h of running at full brightness
- 4 hours to fully charge from empty-to-full
- Battery capacity: 1500 mA
- Type of protection: IP22

Product features

- Convenient button for switching modes
- Fluorescent lens- easy to find in the dark.

TECHNICAL DATA

Electrical data

Nominal wattage	3.20 W
-----------------	--------

Photometrical data

Luminous flux	300 lm
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	80

Dimensions & Weight

Diameter	40.20 mm
Height	166.20 mm
Product weight	190.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP22
Dimmable	No
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

Battery size [GMS]	18650
--------------------	-------

EQUIPMENT / ACCESSORIES

- USB C cable

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854175800	Folding box 1	49 mm x 49 mm x 170 mm	206.00 g	0.41 dm ³
4099854175817	Shipping box 48	307 mm x 213 mm x 371 mm	10339.00 g	24.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.