

PRODUCT DATASHEET FLASHLIGHT TACTICAL IP65

FLASHLIGHT TACTICAL IP65 | Outdoor mobiles



Areas of application

- Multifunctional

Product benefits

- 4 operating modes: 1 press: bright light 1400 lm, 2nd press: soft light 450 lm, 3rd press: SOS mode, 4th press: flashing mode
- The angle of the light beam is adjusted by turning the lens
- 4 hours of running at full brightness
- Powered by 6 AAA batteries (not included)
- Type of protection: IP65 (with closed rotary lens adjustment mechanism)

Product features

- Sturdy aluminum housing
- Convenient button for switching modes

TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
-----------------	---------

Photometrical data

Luminous flux	1400 lm
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	80

Dimensions & Weight

Diameter	46.30 mm
Height	186.30 mm
Product weight	320.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP65/IP20
Dimmable	No
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854175848	Folding box 1	59 mm x 59 mm x 206 mm	346.00 g	0.72 dm³
4099854175855	Shipping box 24	367 mm x 253 mm x 235 mm	8953.00 g	21.82 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.