

PRODUCT DATASHEET FLASHLIGHT COMPACT

FLASHLIGHT COMPACT | Outdoor mobiles



Areas of application

- Multifunctional

Product benefits

- 3 operating modes: 1 press: bright light 400 lm, 2nd press: soft light 120 lm, 3rd press: flashing mode
- 4 hours of running at full brightness
- 7 hours to fully charge from empty-to-full
- Battery capacity: 3000mAh
- Stylish design

Product features

- Rugged and durable housing: IPX2 and can withstands drop test up to two meters
- USB-port with Powerbank function
- Durable and high-quality materials
- Magnet and hook (easy to install under the hood of the car; hanging in a closet or camping tent)

TECHNICAL DATA

Electrical data

| | |
|-----------------|--------|
| Nominal wattage | 4.00 W |
|-----------------|--------|

Photometrical data

| | |
|---------------------------|------------|
| Luminous flux | 400 lm |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | 80 |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 113.00 mm |
| Width | 68.00 mm |
| Height | 26.50 mm |
| Product weight | 145.00 g |

Materials & Colors

| | |
|-----------------|----------------------------------|
| Product color | Orange |
| Housing color | Orange |
| Body material | ABS I TPR (Thermoplastic rubber) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|-----------------|
| Ambient temperature range | -20...+40 °C |
| Type of connection | USB Type-C |
| Type of protection | IPX2 |
| Dimmable | No |
| LED module replaceable | Not replaceable |

Lifespan

| | |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
|---------------------------|-----------------------|

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

| | |
|--------------------|--------|
| Battery size [GMS] | Others |
|--------------------|--------|

EQUIPMENT / ACCESSORIES

– USB C cable

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854175473 | Blister 1 | 150 mm x 220 mm x 28 mm | 154.00 g | 0.92 dm ³ |
| 4099854175480 | Shipping box 40 | 300 mm x 245 mm x 345 mm | 6541.00 g | 25.36 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.